

AURORA SCONCE 24"/30"/36"/42"/48"

MODELS 10875, 10876, 10877, 10878, 10879

The Aurora Sconce's refined aesthetics and unmatched functionality create an impeccable blend of style and performance for your interior spaces. It is perfect for powder and dressing rooms, whether mounted vertically or horizontally. The 270-degree manual rotation, allows you to position the light precisely where you want it. The Aurora Sconce is available in custom lengths and signature bronze finishes.

MATERIAL

Architectural Bronze

FINISHES

Earthen Bronze, Antiqued Bronze, Blackened Bronze, Satin Bronze, Satin Nickel

LAMPING/ DIMENSIONS

10875 LED

11 total watts, Standard 3000K/98+ CRI
~825 Fixture Lumens Universal 120-277V.
W 1" x L 24" x Projection 3.5"
7 lbs
(25mm x 610mm x 90mm)
3.2 kg

10876 LED

14 total watts, Standard 3000K/98+ CRI ~1100 Fixture Lumens Universal 120-277V. W 1" x L 30" x Projection 3.5" (25mm x 762mm x 90mm)

10877 LED

16 total watts, Standard 3000K/98+ CRI ~1250 Fixture Lumens Universal 120-277V. W 1" x L 36" x Projection 3.5" 9 lbs (25mm x 914mm x 90mm) 4 kg

8 lbs


3.6 kg

10878 LED

20 total watts, Standard 3000K/98+ CRI ~1500 Fixture Lumens Universal 120-277V. W 1" x L 42" x Projection 3.5" 10 bs (25mm x 1067mm x 90mm) 4.5 kg

10879 LED

27 total watts, Standard 3000K/98+ CRI
~2100 Fixture Lumens Universal 120-277V.
W 1" x L 48" x Projection 3.5" 11 lbs
(25mm x 1219mm x 90mm) 5kg







NOTES

- UL listed (or equivalent) for damp locations.
- 2700K color temperature is available
- Backplates: 2"ø x 3/8" (51 x 10mm) or a 1.25" ø trim plate on premium mud style and mirror mounting.



- Light Bar has a half-round lens, creating a 1" round profile.
- 270 degree manual rotation
- The lamps standard in this fixture can be dimmed with ELV or MLV style dimmers.
- Driver must be mounted remotely.
- · End Cap Style: Knurled or Smooth.