


B O Y D




ELEMENTS: WATER
LED IN-WALL

#10675

10675 Elements: Water LED In-Wall 3'

Height	Width	Projection	Net Wt.
36 ⁵ / ₈ "	5 ⁵ / ₈ "	1 ¹ / ₈ "	16 lbs
930 mm	143 mm	3 mm	7.3 kg



Backbox: 5" H x 36" W x 3¹/₄" D;
127 mm x 914 mm x 83 mm

Center of outlet box to top of fixture:
18¹/₄"; 464 mm

Reflector: Mirrored panel with clear half-spheres

Cover Lens: Two-way mirror

Combination of mirrored panel and two-way mirrored cover lens creates an infinity reflection

Backbox: unfinished aluminum

Outer Frame: available in White Primer for painting (standard), or Blackened Steel (upcharge)

Horizontal or vertical mounting

This fixture requires recessed mounting. See full installation instructions for mounting details.

ADA compliant at all mounting heights

UL listed (or equivalent) for damp locations

REQUIRED INFORMATION

- Length: 36" nominal or 48" nominal



LAMPING

LED

- 2700°K / 90+ CRI
- 40 total watts
- Lamp included with fixture

Fixture can be dimmed using 0-10v low-voltage dimming controls and wiring

STANDARD FINISHES


- Outer Frame**
- White Primer

OPTIONAL

- Outer Frame**
- Blackened

10675 Elements: Water LED In-Wall 4'

Height	Width	Projection	Net Wt.
48 ⁵ / ₈ "	5 ⁵ / ₈ "	1 ¹ / ₈ "	21 lbs
1235 mm	143 mm	3 mm	9.5 kg



Backbox: 5" H x 48" W x 3¹/₄" D;
127 mm x 1219 mm x 83 mm

Center of outlet box to top of fixture:
24¹/₄"; 616 mm

Reflector: Mirrored panel with clear half-spheres

Cover Lens: Two-way mirror

Combination of mirrored panel and two-way mirrored cover lens creates an infinity reflection

Backbox: unfinished aluminum

Outer Frame: available in White Primer for painting (standard), or Blackened Steel (upcharge)

Horizontal or vertical mounting

This fixture requires recessed mounting. See full installation instructions for mounting details.

ADA compliant at all mounting heights

UL listed (or equivalent) for damp locations

REQUIRED INFORMATION

- Length: 36" nominal or 48" nominal



LAMPING

LED

- 2700°K / 90+ CRI
- 56 total watts
- Lamp included with fixture

Fixture can be dimmed using 0-10v low-voltage dimming controls and wiring

STANDARD FINISHES

- Outer Frame**
- White Primer

OPTIONAL

- Outer Frame**
- Blackened