

# ELEMENTS: FIRE LED IN-WALL


#10674

SHOWN IN 22K YELLOW GOLD LEAF REFLECTOR

AND BLACKENED FRAME

### 10674 Elements: Fire LED In-Wall 3'

Height Width Projection Net Wt. 1/8" 365/8" 55/8" 16 lbs 930 mm 143 mm 3 mm 7.3 kg



Backbox	5" H x 36" W x 3 <sup>1</sup> / <sub>4</sub> " D;	
	127 mm x 914 mm x 83	mm

Center of outlet box to top of fixture:

18<sup>1</sup>/<sub>4</sub>"; 464 mm

Reflector: brass plate gilded with gold

Backbox: unfinished aluminum

Outer Frame: available in White Primer for painting (standard), or Blackened Steel (upcharge)

Horizontal or vertical mounting

This fixture requires recessed mounting. See full installation instructions for mounting details.

ADA compliant at all mounting heights

UL listed (or equivalent) for damp locations

Optional Cover Lens: clear acrylic (upcharge)

# REQUIRED INFORMATION

• Length: 36" nominal or 48" nominal



# LAMPING

#### LED

- 2700 K / 90+ CRI
- 40 total watts
- · Lamp included with fixture

Fixture can be dimmed using 0-10v low-voltage dimming controls and wiring

# STANDARD FINISHES

# **Outer Frame**

• White Primer

#### Inner Reflector Panel

- 22k Yellow Gold Leaf
- 12k White Gold Leaf

# **OPTIONAL**

## **Outer Frame**

Blackened


#### Cover Lens

clear acrylic


10674 Elements: Fire LED In-Wall 4'

48<sup>5</sup>/8"





5<sup>5</sup>/8"



Center of outlet box to top of fixture: 24<sup>1</sup>/<sub>4</sub>"; 616 mm

Reflector: brass plate gilded with gold leaf

Backbox: unfinished aluminum

Outer Frame: available in White Primer for painting (standard), or Blackened Steel (upcharge)

Horizontal or vertical mounting

This fixture requires recessed mounting. See full installation instructions for mounting details

ADA compliant at all mounting heights

UL listed (or equivalent) for damp locations

Optional Cover Lens: clear acrylic (upcharge)

# REQUIRED INFORMATION

• Length: 36" nominal or 48" nominal



# LAMPING

- 2700 K / 90+ CRI
- 56 total watts
- · Lamp included with fixture

Fixture can be dimmed using 0-10v low-voltage dimming controls and wiring

# STANDARD **FINISHES**

# **Outer Frame**

· White Primer

#### Inner Reflector Panel

- 22k Yellow Gold Leaf
- 12k White Gold Leaf

# OPTIONAL

# **Outer Frame**

Blackened

# **Cover Lens**

· clear acrylic

DENNIS MILLER ASSOCIATES

200 Lexington Avenue Suite 1210 New York, NY 10016 212.684.0070 Fax.212.684.0776 www.dennismiller.com